



Stormshield Quick Dry Stabilising Solution

DESCRIPTION

Johnstone's Trade Stormshield Quick Dry Stabilising Solution is a penetrating solution formulated for application to surfaces of a highly porous or friable nature. It provides a substrate suitable for further decoration with paints such as Johnstone's Trade Stormshield Smooth Masonry, Textured Masonry and Jontex High Build Masonry finishes.

RECOMMENDED USES



Suitable for interior and exterior use.

TYPE OF SUBSTRATE

Concrete, cement rendering, brick, stone, blockwork and pebble dash.

COLOUR RANGE

Clear (once dry).

FINISH

Not Applicable.

VOLUME SOLID

9%

COVERAGE



Johnstone's Trade Stormshield Quick Dry Stabilising Solution will cover approximately 6-10 square metres per litre depending on the nature and porosity of the surface being coated.

FILM THICKNESS

Wet: not applicable, dry: not applicable.

DRYING TIME



Touch dry in 1-2 hours. Recoatable after 2 - 4 hours under normal drying conditions.

TRANSPORTATION & STORAGE


To avoid the risk of spillage, always store and transport in a secure upright position. PROTECT FROM FROST

THINNER

Thinner: Clean water.

VOC CONTENT

EU limit value for this product (Cat A/h): 30g/l (2010). This product contains max 3g/l VOC.



KEY PROPERTIES

- Primes porous surfaces
- Highly penetrative
- Recoat in 2-4 hours

PREPARATION

All surfaces to be stabilised should be clean, dry and free from loose and flaking material. Repair cracks and defective areas and treat fungal or algal growth with Johnstone's Trade Sterilisation Wash as directed. Any limewash or distemper should be completely removed. Wear a suitable face mask when creating dust. DO NOT use Johnstone's Trade Stormshield Quick Dry Stabilising Solution on new/sound surfaces. Apply a thinned coat of Johnstone's Trade Stormshield Quick Dry Masonry Paint (see can for details). For more information and free Johnstone's Trade datasheets call 01924 354354 or visit www.johnstonestrade.com.

APPLICATION



Ensure good ventilation during application and drying. Do not breathe spray. Wear respiratory protection. Stir well. Easy to apply by brush or roller. Also suitable for spraying. Not suitable for use on non-absorbent surfaces. Work the primer well into the surfaces. Do not apply under conditions of less than 10°C or externally when rain is imminent. The product will appear pale blue in the container to enable the user to observe which areas have been coated. The product dries clear.

CLEANING



Remove as much product as possible from the application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- Keep out of reach of children
- Avoid contact with skin and eyes
- Do not ingest
- Do not breathe spray. Wear respiratory protection
- If medical advice is needed have container or label to hand
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency
- SDS available : www.johnstonestrade.com or call 01924 354354

SIZES

5 Litre.



For more information on our products and services call 01924 354354 or visit www.johnstonestrade.com.