

DESCRIPTION

Johnstones Trade Stormshield Stabilising Solution is a penetrating solution formulated for application to external masonry surfaces of a highly porous or friable nature. It creates a substrate suitable for further decoration with water-borne paints such as Johnstones Trade Stormshield Smooth, Textured and Jontex High Build Masonry Finishes.

RECOMMENDED USES



TYPE OF SUBSTRATE

Concrete, cement rendering, brick, stone, blockwork and pebble dash.

COLOUR RANGE

White and Clear.


FINISH

Not Applicable.

VOLUME SOLID

22%


COVERAGE



FILM THICKNESS

Wet: not applicable, dry: not applicable.

DRYING TIME



TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position. **STORE AWAY FROM HEAT AND FLAME.**

CLEANER

Thinner: White spirit.

VOC CONTENT

EU limit value for this product (Cat A/h): 750g/l (2010). This product contains max 750g/l VOC.



KEY PROPERTIES

- Primes porous surfaces
- Highly penetrative

PREPARATION

All surfaces to be stabilised should be clean, dry and free from loose and flaking material. Repair cracks and defective areas and treat fungal or algal growth with Johnstone's Trade Sterilisation Wash as directed. Wear a suitable face mask when creating dust. For more information and free Johnstone's Trade datasheets call 01924 354354 or visit www.johnstonestrade.com.

APPLICATION



Ensure maximum ventilation during application and drying. Stir well. Easy to apply by brush or roller. Not suitable for use under solventborne or oil-based products or on non-absorbent surfaces. Apply one coat of Johnstone's Trade Stabilising Solution liberally to a small test area. If this dries to a glossy film thin with one part White Spirit to two parts of Johnstone's Trade Stabilising Solution and then test again in another small area. It is important to ensure that a non-glossy, dried sealed surface is produced.

CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with White Spirit or Turpentine Substitute. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- Keep out of reach of children
- Avoid contact with skin and eyes
- Do not ingest
- If medical advice is needed have container or label to hand
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency
- SDS available : www.johnstonestrade.com or call 01924 354354

SIZES

5 Litre.



The British Board of Agrément is designated by Government to issue European Technical Approvals based on the assessment of products for construction. Johnstone's products carrying this logo have undergone rigorous independent testing and received approval from the BBA.