

## BREWERS CONTRACT MATT

Brewers Contract Matt is a high opacity, low odour, water based paint formulated for interior use on walls and ceilings. It provides a smooth matt finish that is ideal for application to new plaster and can also be used on wallboards and other interior masonry surfaces such as brick or block.

<b>Recommended uses</b>	Interior only
<b>Type of substrate</b>	Plaster and embossed wallcoverings. Also suitable for use on wallboards, concrete, brickwork and blockwork.
<b>Colour availability</b>	White and 132 colours (47 BS4800 and 13 RAL) (10ltr)
<b>Finish</b>	Matt
<b>Volume solid</b>	24%
<b>Coverage</b>	Brewers Contract Matt will cover approximately 13 square metres per litre depending on the nature and porosity of the surface. Strong and contrasting colours may require additional coats. When using more than one tin of a colour in the same room, intermix before use.
<b>Drying time</b>	Under normal conditions; touch dry after 1-2 hours, recoatable after 2-4 hours.
<b>Transportation and storage</b>	To avoid the risk of spillage, always store and transport in a secure upright position. Protect from frost. Lift with care - gross weight does not exceed 16 kilograms. Do not use empty container for storing food.
<b>VOC content</b>	MINIMAL VOC CONTENT 0-0.29% VOCs (Volatile Organic Compounds) contribute to atmospheric pollution. EU limit value for this product (Cat A/a): 30g/l(2010). This product contains max 3g/l VOC.
<b>Film thickness</b>	Wet: 90µm Dry: 22µm
<b>Preparation</b>	All surfaces to be painted should be clean, dry and free from loose and flaking material. Prime where required with a suitable Primer Undercoat. Rub down glossy surfaces with fine waterproof abrasive paper and rinse thoroughly. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Seal absorbent surfaces with a solution of up to 1 part water to 9 parts Brewers Contract Matt.
<b>Application</b>	Stir well before use. Do not thin, except for absorbent surfaces, or when applying by roller or spray when a small quantity of clean water may be added. Suitable for application by brush, roller or spray. Apply paint evenly by brush or roller and avoid overspreading. If required, a second coat may be applied after 2 to 4 hours. Ensure good ventilation during application and drying and do not apply in temperatures below 10°C or in damp conditions.
<b>Cleaning</b>	Remove as much product as possible from application equipment before washing. Replace lid firmly. Wash equipment immediately after use with warm soapy water. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

## Warning

- Contains 1,2-benzisothiazol-3(2H)-one and 2-methyl-2H-isothiazol-3-one. May produce an allergic reaction.
- Safety data sheet available on request.
- If medical advice is needed, have product container or label at hand.
- Keep out of reach of children.
- Dispose of contents/container to a waste disposal site in accordance with local/national regulations.
- Do not breathe spray. Wear respiratory protection.
- Ensure good ventilation during application and drying.
- Do not get in eyes, on skin, or on clothing.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- IF ON SKIN: Wash with plenty of water. Do not use solvent thinners or White Spirit.
- IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell.

Before using this product please ensure you have the latest information.

For help or more information contact:

**Brewers**

**Tel** 01323 411080  
**E-mail** enquiries@brewers.co.uk  
**Website** www.brewers.co.uk

This information is correct at date of issue February 2019