

## FAST MATT

**Dulux Trade Fast Matt** is a low sheen interior matt emulsion that delivers excellent touch-up properties and is ideal for painting on plasterboard. The product is ready-for-use and has low splatter.

### KEY BENEFITS

- Ready for Use
- Easy Application & Low Splatter
- Suitable for Dry-Lining

### PRODUCT INFORMATION

#### Typical Use

Suitable for use on any substrates where minimum disruption is desired.

#### Pack Size

10L only.

#### Colour Range

See appropriate **Dulux Trade** colour literature or visit [duluxtrade.co.uk](http://duluxtrade.co.uk)

#### Film Properties

**Chemical Resistance:** Not suitable.

**Heat Resistance:** Not suitable for use on heated surfaces such as radiators.

**Water Resistance:** Where frequent heavy condensation is likely, such as some kitchens and bathrooms, **Dulux Trade** Diamond Eggshell is more suitable.

#### Composition (nominal)

**Pigment:** Lightfast Pigments.

**Binder:** PVA Copolymer Emulsion.

**Solvent:** Water.

#### Volume Solids

White: 30% (nominal), other colours will vary.

### SURFACE PREPARATION

To get the best results, ensure surfaces to be painted are sound, clean and dry. If necessary, wash the surface to remove dirt, grease and powdery or dusty residues. Rinse with clean water and allow to dry. Seal surfaces that remain powdery after thorough preparation with an appropriate plaster sealer.

Remove all loose and defective paint. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead.

Any surface defects should be filled with the appropriate **Polycell Trade Polyfilla**.

### SYSTEMS INFORMATION

**STIR THOROUGHLY BEFORE USE.** Suitable for painting over skimmed plaster after 24-48 hours. A good visual test to the suitability of the plaster to be painted is when it has started to turn from brown to pink.

The normal finishing process is 2 full coats of Dulux Trade Fast Matt. Thinning is not usually required but may be thinned up to 1 part clean water to 10 parts paint if desired under normal conditions, or up to 1 part clean water to 5 parts paint when applying over a porous substrate.

For best colour consistency, purchase sufficient tinted paint for each job including touch-in at one time from the same source.

### APPLICATION METHOD

Brush, roller, conventional spray and airless spray. A medium pile roller is the most suitable for water-based wall coatings.

As with other water-based paints, do not apply in temperatures below 8°C (as recommended by British Standard BS 6150).

#### Practical Coverage

A guide to the practical coverage which can be achieved under normal conditions is up to 17m<sup>2</sup> per litre.

#### Thinning

**Sealing new or bare surfaces:** Add up to 1 part clean water to 5 parts paint.

**Conventional spray application:** Add up to 1 part clean water to 2.5 parts paint

**Airless spray application:** Add up to 1 part clean water to 5 parts paint.

## FAST MATT

### Spray Recommendations

**Conventional Spray:** Satisfactory through most equipment.

**Airless Spray:** A typical set up for airless spray application would be a minimum working pressure on paint of 133 bars (2000 lb/sq in) with a spray tip size of 0.38mm (15 thou) and a spray tip angle of 65°.

### Drying Times

*Single coat at standard thickness:*

**Touch Dry:** Dependent on temperature and humidity.

**Recoat:** 2-4 hours.

### Cleaning Up

After use, remove as much product as possible from equipment before cleaning with water.

When this paint container is empty please ask your stockist about recycling. If you have leftover paint, please dispose of it responsibly and consider donating it to **Community RePaint**. Find out more at [duluxtrade.co.uk/pp](http://duluxtrade.co.uk/pp).

### Transportation & Storage

Do not use or store in extremes of temperature and protect from frost. To prevent spillage, please store and transport upright.

### VOC

EU limit value for this product (cat.: A/a): 30g/l (2010).

**Ready Mixed:** This product contains max. 1g/l VOC. VOC content: Minimal (0-0.29%).

**Tinted Colour:** This product contains max. 3g/l VOC. VOC content: Minimal (0-0.29%).

## FURTHER SUPPORT

If you need further support, please contact the **AkzoNobel** Technical Advice Centre on [08444 817 818](tel:08444817818).

**Always read full Health, Safety & Environmental Information on can before use.**

Safety datasheet (SDS 515) is available free on request by telephoning the **AkzoNobel** Technical Advice Centre or by visiting [duluxtrade.co.uk](http://duluxtrade.co.uk).

AkzoNobel, the AkzoNobel logo, the Flourish logo, Dulux Trade, Polycell, Polyfilla, Community RePaint and the Planet Possible logo are trademarks of the AkzoNobel group. © AkzoNobel 2014.