

READY TO USE FILLER

READY MIXED

REPAIRS ON WALLS & CEILINGS

- ◆ EASY TO APPLY
- ◆ EASY TO SAND
- ◆ NO NEED TO SPOT PRIME
- ◆ WILL NOT FLASH OR GRIN



PURPOSE

Ready to use interior filler for repairs, gaps, cracks on walls and ceilings.

SUBSTRATES

Ready To Use Filler can be applied to any substrates either unpainted or painted:

- Gypsum plaster, plasterboards/drywall lining
- Old painted surfaces, cement, concrete, cellular concrete
- Breeze blocks, bricks, stone and primed wood.

OVERCOATING

Ready To Use Filler can be overcoated with any type of filler, paint or wall coating.

Physical and technical FEATURES

- Ready To Use Filler: filler in ready mixed form for interior use, made of mineral extracts and selected resin.
- Characterization (NFT 36-005): Family III - class 2.
- Codification (EN 16-566): G₃S₂V₀W₀A₀C₀R₀.
- Mixing rate: ready to use.
- Application thickness: up to 1cm.
- Capacity: 1kg fills 0.65L.
- Setting time: second coat as soon as the filler is hard and dry to the touch.
- Overcoating: can be painted in 12 to 24 hours average time (after complete drying).
- Color: white.
- Adhesion: filler/substrate (EN 16-566): > 0.5 Mpa.

USE AND STORAGE CONDITIONS

- Application tools: filling knife, trowel or blade.
- Tool cleaning: after use, product residue can be rubbed off tools when dry (water cleaning is not necessary).
- Preservation: product guaranteed 12 months. Stored away from sunlight and frost. If found to be faulty within the guarantee period, we will arrange a replacement on proof of purchase.

PACKAGING

Tube: 330g

Tub: 1.5kg and 4kg.

RECOMMENDATIONS and care for use

The times mentioned are indicative and depend on the substrate, coat thickness, and the ambient conditions.

Do not apply at a temperature below 8°C or above 35°C nor at a relative humidity over 70%.

SUBSTRATES PREPARATION

Substrates to be prepared as per the current trade practices. Substrates must be hard, cohesive, clean, sound and dry.

NORMATIVE DOCUMENTS to be referred to

- BS EN 16566:2014 (Paints and varnishes. Fillers for internal and/or external works).
- NF Environment – Paint fillers (NF446).

HEALTH AND SAFETY

It is recommended to wear gloves and glasses while applying Ready To Use Filler.

Always wear a dust mask when sanding.

Dispose of unused product and packaging responsibly at your local waste collection centre.

Preservatives: Contains 1,2-benzisothiazolin-3-one; C(M)IT / MIT (3:1); MBIT.

May produce an allergic reaction.

Safety data sheet available at www.toupret.co.uk

The data sheet information, especially the guidelines relevant to the application and final use of the product are provided in good faith and result from TOUPRET's experience and knowledge of the products. The product should be used as per the trade practices rules book and in reference to our recommendations. The information provided is relevant to applications processed at a temperature of 20°C, a relative humidity of 50% and on average absorbency substrates. The times mentioned are only indicative and depend on the substrate, the coat thickness, and the ambient conditions.



* Information on the emission level of volatile substances into indoor air, presenting a risk of toxicity by inhalation, on a scale from A+ (very low emissions) to C (high emissions).