



Issued 10/21

1015

AIRSURE VINYL MATT

Dulux Trade Airsure Vinyl Matt is a top quality, high opacity emulsion which gives excellent coverage with a high quality finish. **Dulux Trade Airsure** Vinyl Matt is also 99.9% VOC Free*, to minimise the impact on indoor air quality**. Suitable for all normal interior wall and ceiling surfaces.

* Based on in-can VOC content, measured in accordance with ISO 11890-2:2013.

** Independently tested for emissions, including formaldehyde, TVOC, TSVOC and Cat 1A & 1B carcinogens. See VOC section for more detail

KEY BENEFITS

- 99.9% VOC Free*, to minimise the impact on indoor air quality**
- Excellent Application and Finish
- High Opacity
- BREEAM NC 18 & LEED V4.1 compliant, and contributes toward satisfying Feature XO6 (VOC restrictions) under the WELL Building Standard®

PRODUCT INFORMATION

Typical Use

Suitable for interior use on all normal interior wall and ceiling surfaces. For interior areas that are likely to suffer from mould growth, use **Mouldshield** Fungicidal Matt or Eggshell* from **Dulux Trade**.

Pack Size

10L.

Colour Range

White & RAL9010

Film Properties

Chemical Resistance: Not suitable.

Heat Resistance: Not suitable for use on heated surfaces, such as radiators.

Water Resistance: Where frequent heavy condensation is likely, as in some kitchens and

bathrooms, **Dulux Trade** Diamond Eggshell is more suitable.

Composition (nominal)

Pigment: Lightfast Pigments.

Binder: Vinyl Copolymer Emulsion.

Solvent: Water.

Volume Solids

White – 33% (nominal). Other colours will vary.

SURFACE PREPARATION

To get the best results with **Dulux Trade Airsure** Vinyl Matt, make sure surfaces to be painted are sound, clean, dry (new surfaces particularly must be fully dry).

Remove all loose and defective paint. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead.

Where necessary, wash the surface to remove dirt, grease and powdery or dusty residues. Rinse with clean water and allow to dry. Seal surfaces that remain powdery after thorough preparation with an appropriate plaster sealer.

Where necessary, rub down and then wipe off with a damp, lint free cloth to avoid dust.

VINYL MATT

Any surface defects should be filled with the appropriate **Polycell Trade Polyfilla**.

SYSTEMS INFORMATION

STIR THOROUGHLY BEFORE USE. Seal new or bare surfaces with a thinned first coat of **Dulux Trade Airsure Vinyl Matt** (up to 1 part clean water to 5 parts paint). The normal finishing process is 2 full coats of **Dulux Trade Airsure Vinyl Matt**, however for significant colour change additional coats may be required.

For best colour consistency, purchase sufficient tinted paint for each job including touch-in at one time from the same source.

APPLICATION METHOD

Brush, roller or airless spray.

As with other water-based paints, do not apply at temperatures below 8°C (as recommended by British Standard BS 6150).

To minimise picture framing or patchy finishes, we strongly recommend stirring the paint thoroughly prior to use. If thinned, the paint used for cutting-in and for rolling should be to the same ratio. Cut in one wall at a time, then rolling immediately afterwards, not allowing the cutting-in to dry prior to rolling. Cut in no more than 5 to 8cm away from any internal angles, including sockets/switches, skirting, architraves, etc. Roll into the cutting-in, ensuring you roll as close to the edge as possible.

Practical Coverage

A guide to the practical coverage which can be achieved under normal conditions is up to 17m² per litre.

Thinning

Sealing new or bare surfaces: Add up to 1 part clean water to 5 parts paint.

Normal use (not to be exceeded): Add up to 1 part clean water to 10 parts paint.

Airless spray application: Add up to 1 part clean water to 9 parts paint.

Spray Recommendations

Airless Spray:

Pressure: approx. 2200 - 2500 psi

Tip size: 517 or 519

The above settings are an indication only. To get the best results, it is advised to tune the settings to suit the site conditions and should be assessed by means of a test area. For more complex surfaces/areas, the use of a Low Pressure or Fine Finish tip should be considered.

Drying Times

Single coat at standard thickness:

Touch Dry: Dependent on temperature and humidity.

Recoat: 2-4 hours.

Cleaning Up

After use, remove as much product as possible from equipment before cleaning with water.

When this paint container is empty please ask your stockist about recycling. If you have leftover paint, please dispose of it responsibly and consider donating it to **Community RePaint**. Find out more at

www.duluxtradepaintexpert.co.uk/products/sustainability.



Issued 10/21

1015

AIRSURE VINYL MATT

Transportation & Storage

Do not use or store in extremes of temperature and protect from frost. To prevent spillage, please store and transport upright.

VOC

EU limit value for this product (cat.: A/a): 30g/l (2010).

This product contains max. 0.5g/l VOC.

VOC content: Minimal (0-0.29%).

Emissions:

This product is considered "Low" for emissions, and has been independently tested by Eurofins, following the Indoor Air Comfort Gold test which

is based on ISO 16000 / EN 16402, for Formaldehyde, Total Volatile Organic Compounds (TVOCs) and Carcinogens. It is BREEAM NC 18 & LEED V4.1 compliant, and contributes toward satisfying Feature X06 (VOC restrictions) under the WELL Building Standard®. Please ask for further details.

Carbon Footprint;

White; 1.243CO²ekg/L based on cradle to grave life cycle assessment.

An EPD (Environmental Product Declaration) is also available for this product. Please visit the 'Datasheets and Documents' section of the specific product page at duluxtrade.co.uk

FURTHER SUPPORT

If you need further support, please contact the **AkzoNobel** Technical Advice Centre on [0333 222 70 70](tel:0333 222 70 70).

* **Mouldshield** Fungicidal Matt and Eggshell from **Dulux Trade** contains: 3-iodo-2-propynyl-n-butyl carbamate.

Use biocides safely. Always read the label and product information before use.

Always read full Health, Safety & Environmental Information on can before use.

Safety datasheet is available free on request by telephoning the **AkzoNobel** Technical Advice Centre or by visiting duluxtrade.co.uk.

AkzoNobel, the AkzoNobel logo, the Flourish logo, Dulux Trade, Mouldshield, Polycell, Polyfilla, Airsure and Community RePaint are trademarks of the AkzoNobel group. © AkzoNobel 2020.