

## PRO GRADE PAINT REMOVER



### OVERVIEW

Removes sealers and coatings safely and effectively without damaging the surface. Strips a wide variety of surfaces and coatings including:

Paint & Varnish  
Artex  
Stains & Lacquer  
Graffiti  
Carpet adhesive residues from floors

### APPLICATION

Cover the top with a cloth during opening to avoid splashes.

Layer a generous, even coat of Enviromose onto the surface to be stripped.

Apply with a suitable clean brush or airless spray (rollers can be used for light coatings) **DO NOT BRUSH OUT**

Leave for approximately 2 hours and apply a second generous coat. (On less than five layers of Paint or Varnish, a second coat may not be necessary).

After the product has penetrated the substrate (up to 24 hours) scrape off with suitable scrapers, leaving surface as clean as possible.

Rinse clean with cold water containing detergent and a stainless steel scourer, leave to dry. Never use steel wool - stainless steel only.

### GUIDE OF STRIPPING TIMES

Varnish: 15 - 60 minutes  
Paint: 10 - 60 minutes  
Two pack varnish: 30 minutes - 3 Hours  
Heavy multi-layered paint: 90 minutes - Overnight  
Two pack lacquer: 30 minutes - 24 Hours  
Graffiti: 5 minutes - 4 Hours  
Artex: 1 - 4 Hours

### PRODUCT CHARACTERISTICS

Colour	Clear
Odour	Barely perceptible
Form	Liquid
Specific Gravity @ 25°C	1.01
PH	11
Application Temperature s	Minimum +5°C Maximum 30°C
Shelf Life	24 months from the date of manufacture in the original unopened container
Coverage	1 litre will strip 1-3 m <sup>2</sup> dependant on thickness and amount of layers / coatings to be stripped

### BENEFITS

For internal & external use  
Safer and easy to use  
Water based and non-flammable  
Non-corrosive, non-ozone depleting  
Extra strong for tougher finishes  
Fast acting  
Eco-friendly  
Low VOC

### CLEANING OF EQUIPMENT

Remove as much excess product as possible and clean tools and equipment immediately after use with soapy water.

### PRECAUTIONS FOR USE

For Health & Safety instructions, first aid measures, spillages and disposal instructions, see separate Health & Safety Data Sheet (MSDS)



## **SURFACE PREPERATION**

Always test an inconspicuous area before use to ensure the compatibility and finished result is acceptable. Ensure the surface(s) to be stripped are dry before applying the Enviromose Pro Grade Paintstripper. Protection should be provided for floor coatings that you do not wish to remover or any surface that may be damaged by the remover i.e. perspex, plastics, rubber etc.