



STABILISING PRIMER

AM301

Issued December 2018

NEW VERSION: Can be identified by the barcode: 5010212647967

PRODUCT DESCRIPTION & USE

Armstead Trade Stabilising Primer is a professional quality, clear solvent-based primer, formulated to seal powdery exterior masonry surfaces that can be used with most decorative finishes.

KEY BENEFITS

- Seals porous, dry & powdery surfaces
- Resists alkali attack
- Use with Armstead Trade Masonry finishes

PACK SIZES



COLOUR RANGE

Clear.

COMPOSITION (NOMINAL)

Pigment: N/A.

Binder: Acrylic Copolymer **Solvent:** White Spirit.

VOLUME SOLIDS

9% (nominal).

SURFACE PREPARATION

All surfaces should be thoroughly prepared by vigorous scraping and brushing to remove any loose or flaking paint and dirt. A stiff fibre brush will give better results than a wire brush, as any wire that becomes embedded in the wall will rust, and stain the new paint. Treat any existing mould or organic growth with *Weathershield Multi-Surface Fungicidal Wash. Make good minor defects. Use a sand and cement mix for larger holes and cracks.

Note: Do not seal sound new or bare surfaces with stabilising primer

Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead.

APPLICATION



Brush or roller. For Health and Safety reasons related to all solvent-based paints, spray application is not recommended.

As with other solvent-based paints, do not apply in temperatures below 5°C (as recommended by British Standard BS 6150).

SYSTEM INFORMATION

Shake container vigorously before use.

After suitable preparation, the normal recommendation is to apply one coat of **Armstead Trade** Stabilising Primer to powdery surfaces, followed by the appropriate **Armstead Trade** exterior finishing system.

PRACTICAL COVERAGE



A guide to the practical coverage which can be achieved under normal conditions is up to $10 \, \text{m}^2/\text{litre}$.

DRYING TIMES (SINGLE COAT, STANDARD THICKNESS)



Touch Dry: 2-4 hours* **Recoat:** 16-24 hours*

*These times will be significantly longer in cold damp conditions.

CLEANING UP



After use, remove as much paint as possible from brushes before cleaning white spirit.

TRANSPORTATION & STORAGE

Do not use or store in extremes of temperature and protect from frost. To prevent spillage, please store and transport upright.

VOC

EU limit value for this product (cat.A/h): 750g/l (2007)/750g/l (2010). This product contains max.749g/l VOC.

*Weathershield Multi-Surface Fungicidal Wash contains: Benzalkonium Chloride.

Use biocides safely. Always read the label and product information before use.

VOC Content Very High more than 50%. VOCs (Volatile Organic Compounds) contribute to atmospheric pollution.

FURTHER SUPPORT

Online: www.armsteadtrade.co.uk Email: armstead.advice@akzonobel.com

Phone: 0333-222-70-70

Please visit www.armsteadtrade.co.uk to download safety sheet SDSAM301



Like us on Facebook



Videos on YouTube



Follow us on Twitter

