

TECHNICAL HEALTH AND DATA SHEET

PRODUCT:- METAL PRESERVATIVE PAINT

REFERENCE:- G/123/1043

COLOUR:- RUST RED

FINISH:- GLOSS

TYPE:- MODIFIED THIXOTROPIC ALKYD

TYPICAL SG:- 1.0 AT 20 C

TYPICAL VISCOSITY:- 4.0 POISE AT 25 C

TYPICAL TOTAL SOLIDS:- 54.7% BY WEIGHT

FLASH POINT:- APPROX. 40 C

RECOMMENDED THINNERS:- V/607/14

APPLICATION:- BY BRUSH

*COVERAGE GUIDE:- 14 SQ. METRES/LITRES

*DRYING TIME:- SURFACE DRY - 4 HOURS
THROUGH DRY - 18 HOURS

USES:- AS AN ECONOMICAL
PROTECTIVE
FOR METALWORK

HEALTH & SAFETY:- SEE SHEET HSD 'A'

NOTE:- OTHER COLOURS AVAILABLE, SOME
CONTAINING LEAD WHEN SHEET
HSD 'C' WOULD APPLY.

*BY BRUSH TO A DRIED FILM THICKNESS OF 20 - 25 MICRONS AT 20 C

Teamac® Paints

MANUFACTURERS OF DECORATIVE, MARINE AND INDUSTRIAL
COATINGS

Teal & Mackrill Limited,
Lockwood Street, HULL. HU2 OHN
Telephone: 01482-320194 Fax: 01482-219266