



BY APPOINTMENT TO HER MAJESTY THE QUEEN
PURVEYORS OF FABRICS, PAINTS & WALLPAPERS
SANDERSON, CHELSEA, LONDON

SANDERSON

ACTIVE EMULSION

DESCRIPTION

Active Emulsion is ideal for corridors, kitchens, bathrooms and playrooms, this highly durable emulsion is suitable for interior walls and ceilings. With a sheen of less than 5%, this high-performance, washable paint delivers a classic matt finish with a smooth, refined aesthetic.

KEY PROPERTIES

- Ultimate durability and performance.
- This is wipeable and washable due to its scrub resistance
- Ideal for high wear/traffic areas such as hallways, kitchens and children's bedrooms.
- Low sheen finish

PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material including dirt and grease. Prime base surfaces with an appropriate primer. Rub down previously painted surfaces with fine waterproof abrasive paper and rinse thoroughly. Avoid the inhalation of dust and wear a suitable face mask if dry sanding. Special precautions should be taken during preparation of pre-1960's paint surfaces as they may contain harmful lead.

APPLICATION

Stir well before use. Ensure good ventilation during application and drying. Apply by brush, roller or sprayer. Do not overfill paint trays. Ensure roller is loaded evenly. If using a brush, load generously. Apply liberally and evenly; avoid overspreading. Apply two coats. Additional coats may be required on new plaster or where a greater colour change is desired. Do not apply in temperatures below 10°C or in damp conditions. If more than one can of colour is to be used in the same area, intermix before use.

CLEANING

Remove as much product as possible from equipment before cleaning. Replace lid firmly. Clean equipment immediately after use in warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty waste paint into drains or watercourses.

PRECAUTIONS

- Contains reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1). May produce an allergic reaction. Safety data sheet available on request. If medical advice is needed, have product container or label at hand.
- Keep out of reach of children.
- Dispose of contents/container to a waste disposal site in accordance with local/national regulations.
- Ensure good ventilation during application and drying.

- Do not get in eyes, on skin, or on clothing.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- IF ON SKIN: wash with plenty of water. Do not use solvent thinners or White Spirit.
- IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell. Safety data sheet available on request.

RECOMMENDED USES

Suitable for interior use.

TYPE OF SUBSTRATE

Interior walls and ceilings.

Can also be used on suitably primed wood panelling.

COLOUR RANGE

154 colours.

FINISH

Low sheen - Less than 5%.

VOLUME SOLID

29%.

COVERAGE

Approximately 12 square metres per litre depending on the nature and porosity of the surface.

DRYING TIME

Touch dry in 1 - 2 hours. Recoatable after 2 - 4 hours.

TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position. Protect from frost, store away from heat and flame.

CLEANER

Clean water.

VOC CONTENT

- Low VOC (Volatile Organic Compounds) 0.3 - 7.99%
- EU limit value for this product Cat A/(a): 30 g/L (2010).
- This product contains max 10 g/L VOC.

FILM THICKNESS

Wet: 86µm, Dry: 25µm.

SIZES

2.5 Litre, 5 Litre.