



ZOFFANY

ACRYLIC EGGSHELL

DESCRIPTION

Zoffany Acrylic Eggshell is a premium quality, water based product. Offering superb coverage, this hardwearing, water-based acrylic eggshell is suitable for interior ceilings, walls, metal and both indoor and outdoor woodwork. It's self-priming on most surfaces and achieves a low sheen finish ideal for kitchens, bathrooms and conservatories.

KEY PROPERTIES

- A quick drying, low odour, low sheen finish for interior use.
- Produces a smooth, washable surface that resists condensation.
- Tough, durable and non-yellowing.
- High opacity and hardwearing.

PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material including dirt and grease. Prime bare metal surfaces with an appropriate primer. Rub down previously painted surfaces with fine waterproof abrasive paper and rinse thoroughly. Avoid the inhalation of dust and wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead. Allow radiators to cool before painting.

APPLICATION

Stir well before use. Ensure good ventilation during application and drying. Apply two coats by brush, roller or spray. Additional coats may be required on new plaster or where a greater colour change is desired. Do not apply in temperatures below 10°C or in damp conditions. If more than one can of colour is to be used in the same area, intermix before use.

CLEANING

Remove as much product as possible from equipment before cleaning. Replace lid firmly. Clean equipment immediately after use in warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty waste paint into drains or watercourses.

HEALTH & SAFETY

- Contains reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1), 2-methyl-2H-isothiazol-3-one, 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one, 2-octyl-2H-isothiazol-3-one. May produce an allergic reaction.
- If medical advice is needed, have product container or label at hand.

- Keep out of reach of children.
- Dispose of contents/container to a waste disposal site in accordance with local/national regulations.
- Ensure good ventilation during application and drying.
- Do not get in eyes, on skin, or on clothing.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- IF ON SKIN: Wash with plenty of water. Do not use solvent thinners or White Spirit.
- IF SWALLOWED : Call a POISON CENTRE or doctor if you feel unwell.

RECOMMENDED USES

Suitable for interior and exterior use.

COLOUR RANGE

Alchemy of Colour collection, 156 Colours

FINISH

Low Sheen - 10-25%.

VOLUME SOLID

35%.

COVERAGE

Approximately 18 square metres per litre depending on the nature and porosity of the surface.

DRYING TIME

Touch dry in 1 - 2 hours. Recoatable after 2 - 4 hours.

TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position. Protect from frost, store away from heat and flame.

CLEANER

Clean water.

VOC CONTENT

- Low VOC (Volatile Organic Compounds) Content 0.3-7.99%
- EU limit value for this product Cat A/(d): 130 g/L (2010).
- This product contains max 12g/l VOC.

FILM THICKNESS

Wet: 86µm, Dry: 30µm.

SIZES

1 Litre, 2.5 Litre.