

DESCRIPTION

Albany Acrylic Eggshell is a high-quality trade emulsion. Suitable for interior use on a wide range of surfaces, where a durable mid sheen finish is required. Its mould resisting, Class 1 rated formulation makes it ideal for humid areas such as kitchens, bathrooms and utility rooms.

RECOMMENDED USES



Suitable to use internally on Wood, Metal & Plaster. Walls, concrete, cement rendering and blockwork in internal situations.

COVERAGE



A guide to the practical coverage which can be achieved under normal conditions is up to 14-16m² per litre on smooth surfaces.

DRYING TIME



Under normal drying conditions touch dry in 1-2 hours, recoatable after 3-4 hours. Allow for adequate ventilation during the drying period.

PROPERTIES

COMPOSITION

Pigment: Titanium dioxide, coloured pigments and extenders

Binder: Vinyl acetate copolymer

Solvent: Water

FINISH

Mid Sheen

FILM THICKNESS

Wet 83um. Dry 30um.

VOLUME SOLIDS

36% White. Other colours will vary.

FLASH POINT

Not Applicable.

VOC CONTENT

EU limit value for this product (Cat A/a): 30 g/L (2010).

This product contains max 3 g/L VOC.

MINIMAL VOC CONTENT 0.1-0.29%

LIMITATIONS

For interior use only. Do not apply when air or substrate temperatures are likely to fall below 8°C or when relative humidity is above 80% during application or the drying period.

AVAILABILITY



COLOUR RANGE

Available in Albany colour ranges. Refer to current Albany literature for more colour ranges.



PACK SIZES

1, 2.5, 5 Litres.

KEY BENEFITS

- Tough & Washable
- Mould Resisting
- High Traffic

PREPARATION

For best results, apply in accordance with BS 6150: Code of Practice for Painting of Buildings. Ensure all surfaces to be painted are clean, dry and free from dust, grease, loose or flaking material. Bare surfaces should be primed with a suitable primer. Previously gloss-painted surfaces should be thoroughly abraded using fine waterproof abrasive paper and rinsed clean to ensure good adhesion. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding.

APPLICATION

Stir well before use. Apply by brush, roller or spray. Apply two to three coats as required.



THINNING / MIST COAT

For sealing new/bare surfaces add up to 1-part clean water to 10 parts paint.



AIRLESS SPRAY APPLICATION

For normal use thin up to 10%

(1 part water to 10 parts paint).

To achieve best results, use a 515, 517 or 519 tip

@1300-2400 psi (89-207 bar) (Tip dependant)

The above recommendations are intended as a guide only.

CLEANING UP



Remove as much product as possible from equipment before cleaning. Clean equipment immediately after use with warm soapy water and rinse thoroughly.

AFTER-CARE

MAINTENANCE

Between maintenance redecoration surfaces may be washed with a warm water and liquid detergent solution to remove surface dirt.

STORAGE

Avoid temperature extremes and protect from frost. Store and transport upright to prevent spillage.

HEALTH & SAFETY

- When preparing pre-1960s painted surfaces, take special precautions as they may contain harmful lead.
- Avoid contact with skin and eyes.
- Do not ingest.
- Store away from children and animals.
- Keep containers closed. Do not empty into drains, watercourses or septic tanks, including when cleaning tools. Some local authorities provide specialist facilities for the disposal of waste coatings.