

DESCRIPTION

Albany Super Satin is a high-quality water-based satin. Suitable for both interior and exterior wood and metal surfaces where a durable finish is required. It provides excellent opacity and stays whiter for longer compared with traditional solvent based finishes.

RECOMMENDED USES



Suitable to use on Interior and exterior wood and metal.

COVERAGE



A guide to the practical coverage which can be achieved under normal conditions is up to 10-12m² per litre on smooth surfaces.

DRYING TIME



Under normal drying conditions touch dry in 1-2 hours, recoatable after 4-6 hours. Allow for adequate ventilation during the drying period.

PROPERTIES

COMPOSITION

Pigment: Titanium dioxide, coloured pigments and extenders

Binder: Alkyd Emulsion

Solvent: Water

FINISH

Satin

FILM THICKNESS

Wet 91um. Dry 38um.

VOLUME SOLIDS

41.9% White. Other colours will vary.

FLASH POINT

Not Applicable.

VOC CONTENT

EU limit value for this product (Cat A/d): 130 g/L (2010).

This product contains max 50 g/L VOC.

LOW VOC CONTENT 0.30-7.99%

LIMITATIONS

For interior and exterior use. Do not apply when air or substrate temperatures are likely to fall below 10°C or when relative humidity is above 80% during application or the drying period, or externally when rain is imminent.

AVAILABILITY



COLOUR RANGE

Available in Albany colour ranges. Refer to current Albany literature for more colour ranges.



PACK SIZES

1, 2.5 & 5 Litres.

KEY BENEFITS

- Water based
- Good flow and opacity
- Quick drying

PREPARATION

For best results, ensure all surfaces to be painted are clean, dry and free from dust, grease, loose or flaking material. Prime bare wood with Albany Super Primer Undercoat and prime all other bare surfaces with a suitable primer. Previously painted or glossy surfaces should be thoroughly abraded using fine waterproof abrasive paper and rinsed clean to ensure good adhesion. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding.

APPLICATION

Stir well before use. Apply by brush.
Apply one to two coats as required.



THINNING / MIST COAT
N/A



AIRLESS SPRAY APPLICATION
N/A

CLEANING UP



Remove as much product as possible from equipment before cleaning. Clean equipment immediately after use with warm soapy water and rinse thoroughly.

AFTER-CARE

MAINTENANCE

Between maintenance redecoration surfaces may be washed with a warm water and liquid detergent solution to remove surface dirt.

STORAGE

Avoid temperature extremes and protect from frost.
Store and transport upright to prevent spillage.

HEALTH & SAFETY

- When preparing pre-1960s painted surfaces, take special precautions as they may contain harmful lead.
- Avoid contact with skin and eyes.
- Do not ingest.
- Store away from children and animals.
- Keep containers closed. Do not empty into drains, watercourses or septic tanks, including when cleaning tools. Some local authorities provide specialist facilities for the disposal of waste coatings.