

DESCRIPTION

Albany Vinyl Matt is a high-quality trade emulsion. Suitable for a wide variety of new or previously painted interior walls and ceilings where a matt finish is required.

RECOMMENDED USES



Suitable to use on plaster, walls, ceilings, concrete, cement rendering, brickwork and blockwork in internal situations.

COVERAGE



A guide to the practical coverage which can be achieved under normal conditions is up to 17m² per litre on smooth surfaces.

DRYING TIME



Under normal drying conditions touch dry in 1-2 hours, recoatable after 2-4 hours. Allow for adequate ventilation during the drying period.

PROPERTIES

COMPOSITION

Pigment: Titanium dioxide, coloured pigments and extenders

Binder: Vinyl acetate copolymer

Solvent: Water

FINISH

Matt

FILM THICKNESS

Wet 90um. Dry 30um.

VOLUME SOLIDS

53.7% White. Other colours will vary.

FLASH POINT

Not Applicable.

VOC CONTENT

EU limit value for this product (Cat A/a): 30 g/L (2010).

This product contains max 3 g/L VOC.

MINIMAL VOC CONTENT 0.1-0.29%

LIMITATIONS

For interior use only. Do not apply when air or substrate temperatures are likely to fall below 8°C or when relative humidity is above 80% during application or the drying period.

AVAILABILITY



COLOUR RANGE

Available in Albany colour ranges. Refer to current Albany literature for more colour ranges.



PACK SIZES

0.35, 1, 2.5, 5 Litres (7.5 & 10 Litres colour dependent).

KEY BENEFITS

- Great Coverage
- Excellent Opacity
- Great Flow

PREPARATION

For best results, ensure all surfaces to be painted are clean, dry and free from dust, grease, loose or flaking material. Bare surfaces should be primed with a suitable primer. Previously gloss-painted surfaces should be thoroughly abraded using fine waterproof abrasive paper and rinsed clean to ensure good adhesion. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding.

APPLICATION

Stir well before use. Apply by brush, roller or spray. Apply two to three coats as required.



THINNING / MIST COAT

For sealing new/bare surfaces add up to 1-part clean water to 10 parts paint.



AIRLESS SPRAY APPLICATION

For normal use thin up to 10%

(1 part water to 10 parts paint).

To achieve best results, use a 515, 517 or 519 tip

@1300-2500 psi (89-172 bar) (Tip dependant)

The above recommendations are intended as a guide only.

CLEANING UP



Remove as much product as possible from equipment before cleaning. Clean equipment immediately after use with warm soapy water and rinse thoroughly.

AFTER-CARE

MAINTENANCE

Between maintenance redecoration surfaces may be washed with a warm water and liquid detergent solution to remove surface dirt.

STORAGE

Avoid temperature extremes and protect from frost. Store and transport upright to prevent spillage.

HEALTH & SAFETY

- When preparing pre-1960s painted surfaces, take special precautions as they may contain harmful lead.
- Avoid contact with skin and eyes.
- Do not ingest.
- Store away from children and animals.
- Keep containers closed. Do not empty into drains, watercourses or septic tanks, including when cleaning tools. Some local authorities provide specialist facilities for the disposal of waste coatings.