

DESCRIPTION

Albany Acrylic Primer Undercoat is a high quality, quick drying, all-in-one base coat for bare softwood, MDF and plasterboard. It is suitable for interior and exterior use.

RECOMMENDED USES



Suitable to use on Interior and exterior wood and metal.

COVERAGE



A guide to the practical coverage which can be achieved under normal conditions is up to 12-14m² per litre on smooth surfaces.

DRYING TIME



Under normal drying conditions touch dry in 1 hour, recoatable after 2-4 hours. Allow for adequate ventilation during the drying period.

PROPERTIES

COMPOSITION

Pigment: Titanium dioxide, coloured pigments and extenders
Binder: Acrylic Copolymer
Solvent: Water

FINISH

Matt

FILM THICKNESS

Wet 77um. Dry 24um.

VOLUME SOLIDS

23% White.

FLASH POINT

Not Applicable.

VOC CONTENT

EU limit value for this product (Cat A/d): 130 g/L (2010).
This product contains max 3 g/L VOC.
MINIMAL VOC CONTENT 0.1-0.29%

LIMITATIONS

For interior and exterior use. Do not apply when air or substrate temperatures are likely to fall below 10°C or when relative humidity is above 80% during application or the drying period, or externally when rain is imminent.

AVAILABILITY



COLOUR RANGE

Available in the Albany colour ranged. Refer to current Albany literature.



PACK SIZES

1, 2.5 & 5 Litres.

KEY BENEFITS

- Water Based
- High Opacity
- Quick Drying

PREPARATION

For best results, ensure all surfaces to be painted are clean, dry and free from dust, grease, loose or flaking material. Rub down bare timber surfaces with dry glasspaper to remove raised grain and sharp edges. Apply a suitable Knotting Solution to knots and resinous surfaces, and prime bare metal surfaces with the appropriate primer. Previously painted surfaces should be thoroughly abraded using fine waterproof abrasive paper and rinsed clean to ensure good adhesion. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding.

APPLICATION

Stir well before use. Apply by brush, roller or spray.
Apply one to two coats as required.



THINNING / MIST COAT
N/A



AIRLESS SPRAY APPLICATION

For normal use thin up to 10%
(1 part water to 10 parts paint).
To achieve best results, use a 517 tip
@1800-2500 psi (124-172 bar) (Tip dependant)
The above recommendations are intended as a guide only.

CLEANING UP



Remove as much product as possible from equipment before cleaning. Clean equipment immediately after use with warm soapy water and rinse thoroughly.

AFTER-CARE

MAINTENANCE

Between maintenance redecoration surfaces may be washed with a warm water and liquid detergent solution to remove surface dirt.

STORAGE

Avoid temperature extremes and protect from frost.
Store and transport upright to prevent spillage.

HEALTH & SAFETY

- When preparing pre-1960s painted surfaces, take special precautions as they may contain harmful lead.
- Avoid contact with skin and eyes.
- Do not ingest.
- Store away from children and animals.
- Keep containers closed. Do not empty into drains, watercourses or septic tanks, including when cleaning tools. Some local authorities provide specialist facilities for the disposal of waste coatings.