

DESCRIPTION

Albany Satin is a high quality finish for use on new or previously painted wood and metal, including radiators. It provides a durable and washable finish, making it ideal for areas where a stylish and long-lasting decorative look is required.

RECOMMENDED USES



Suitable to use on Interior wood and metal.

COVERAGE



A guide to the practical coverage which can be achieved under normal conditions is up to 20m² per litre on smooth surfaces.

DRYING TIME



Under normal drying conditions touch dry in 4 - 6 hours, recoatable after 16 - 24 hours. Allow for adequate ventilation during the drying period.

PROPERTIES

COMPOSITION

Pigment: Titanium dioxide, coloured pigments and extenders
Binder: Alkyd
Solvent: White Spirit

FINISH

Satin

FILM THICKNESS

Wet 50um. Dry 31um.

VOLUME SOLIDS

61% White. Other colours will vary.

FLASH POINT

48°C Closed Cup

VOC CONTENT

EU limit value for this product (Cat A/d): 300 g/L (2010).
This product contains max 300 g/L VOC.
HIGH VOC CONTENT 25-50%

LIMITATIONS

For interior use. Do not apply when air or substrate temperatures are likely to fall below 10°C or when relative humidity is above 80% during application or the drying period, or externally when rain is imminent.

AVAILABILITY



COLOUR RANGE

Available in the Albany colour ranged. Refer to current Albany literature.



PACK SIZES

1, 2.5 & 5 Litres

KEY BENEFITS

- Durable & Washable
- Excellent Opacity
- Condensation Resistant

PREPARATION

For best results, ensure all surfaces to be painted are clean, dry and free from dust, grease, loose or flaking material. Bare surfaces should be primed with a suitable primer. Previously painted surfaces should be thoroughly abraded using fine waterproof abrasive paper and rinsed clean to ensure good adhesion. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding.

APPLICATION

Stir well before use. Apply by brush or roller.
Apply one to two coats as required.



THINNING / MIST COAT
N/A



AIRLESS SPRAY APPLICATION
N/A

CLEANING UP



Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use with White Spirit or Albany Brush Cleaner.

AFTER-CARE

MAINTENANCE

Between maintenance redecoration surfaces may be washed with a warm water and liquid detergent solution to remove surface dirt.

STORAGE

Avoid temperature extremes and protect from frost.
Store and transport upright to prevent spillage.

HEALTH & SAFETY

- When preparing pre-1960s painted surfaces, take special precautions as they may contain harmful lead.
- Avoid contact with skin and eyes.
- Do not ingest.
- Store away from children and animals.
- Keep containers closed. Do not empty into drains, watercourses or septic tanks, including when cleaning tools. Some local authorities provide specialist facilities for the disposal of waste coatings.