

ULTRA MATT INTERIOR WALLS

Dulux Trade Ultra Matt Interior Walls delivers a non-reflective dead flat matt finish that enhances the look of the interior spaces. It offers outstanding touch-up capabilities and excellent durability, while its high opacity ensures excellent coverage. *Our formula is 99.9% VOC free, based on in-can VOC content and measured in accordance with ISO 11890-2:2020.

Accreditations

BREEAM Compliant	LEED Compliant	WELL Compliant	EPD Available	Reaction to Fire EN 13501-1
In Progress	In Progress	In Progress	YES	In Progress

KEY BENEFITS

- Excellent Durability & High Opacity
- Dead Flat Matt Finish
- Excellent Touching-in Properties
- 99.9% VOC free. Minimal impact on indoor air quality*

PRODUCT INFORMATION

Typical Use

Suitable for interior use on all normal interior wall and ceiling surfaces. For interior areas that are likely to suffer from mould growth, use Dulux Trade Mouldshield Fungicidal Eggshell or DT Durable Kitchen and Bathroom Eggshell **

Pack Size

2.5L, 5L and 10L.

Colour Range

See appropriate **Dulux Trade** colour literature or visit duluxtrade.co.uk.

Film Properties

Chemical Resistance: Not suitable.

Heat Resistance: Not suitable for use on heated surfaces, such as radiators.

Water Resistance: Where surfaces are subject to a high degree of wear and tear and require a greater level of washability, **Dulux Trade** Diamond Eggshell is more suitable.

Composition (nominal)

Pigment: Lightfast Pigments.

Binder: Acrylic Copolymer Emulsion.

Solvent: Water.

Volume Solids

White – 38% (nominal). Other colours will vary.

SURFACE PREPARATION

To get the best results with **Dulux Trade** Ultra Matt Interior Walls, make sure surfaces to be painted are sound, clean, dry (new surfaces particularly must be fully dry).

Remove all loose and defective paint. Special precautions should be taken during surface

ULTRA MATT INTERIOR WALLS

preparation of pre-1990s paint surfaces over wood and metal as they may contain harmful lead.

Where necessary, wash the surface to remove dirt, grease and powdery or dusty residues. Rinse with clean water and allow to dry. Seal surfaces that remain powdery after thorough preparation with an appropriate plaster sealer.

Where necessary, rub down and then wipe off with a damp, lint free cloth to avoid dust.

Any surface defects should be filled with the appropriate **Polycell Trade Polyfilla**.

SYSTEMS INFORMATION

STIR THOROUGHLY BEFORE USE. Seal new or bare surfaces with a thinned first coat of **Dulux Trade Ultra Matt Interior Walls** (up to 1 part clean water to 5 parts paint). The normal finishing process is 2 full coats of **Dulux Trade Ultra Matt Interior Walls**, however for significant colour change additional coats may be required.

For best colour consistency, purchase sufficient tinted paint for each job including touch-in at one time from the same source.

APPLICATION METHOD

Brush, roller or airless spray.

As with other water-based paints, do not apply in temperatures below 8°C (as recommended by the British Standard BS 6150).

To minimise picture framing or patchy finishes, we strongly recommend stirring the paint thoroughly prior to use. If thinned, the paint used for cutting-in and for rolling should be to the same ratio. Cut in one wall at a time, then

rolling immediately afterwards, not allowing the cutting-in to dry prior to rolling. Cut in no more than 5 to 8cm away from any internal angles, including sockets/switches, skirting, architraves, etc. Roll into the cutting-in, ensuring you roll as close to the edge as possible.

Practical Coverage

A guide to the practical coverage which can be achieved under normal conditions is up to 17m² per litre.

Thinning

Sealing new or bare surfaces: Add up to 1 part clean water to 5 parts paint.

Normal use (not to be exceeded): Add up to 1 part clean water to 10 parts paint.

Airless spray application: Add up to 1 part clean water to 5 parts paint.

Spray Recommendations

Airless Spray: For best results use a 515 Low Pressure tip @1300 - 1700 psi (89 – 117 bar). Alternatively, use a 515 tip @ 2000-2400 psi (138 - 165 bar)

Please note that the above recommendations are intended as a guideline only and some adjustments may need to be made to accommodate equipment type & age, substrate type and individual site & atmospheric conditions.

ULTRA MATT INTERIOR WALLS

Drying Times

Single coat at standard thickness:

Touch Dry: Dependent on temperature and humidity.

Recoat: 2-4 hours

Responsible Cleaning

Cleaning After Final Use: Cleaning your brushes and rollers immediately after their final use ensures they can be reused for multiple projects, saving you money and reducing waste.

Cleaning:

1. **Remove Excess Paint:** Scrape off excess paint into container for future projects.
2. **Clean with Warm, Soapy Water:** Use warm, soapy water in a sealed container, such as a bucket or empty tub, to clean your brushes and rollers.
3. **Rinse Thoroughly:** Ensure all soap and paint residues are completely rinsed out into container.
4. **Dry Naturally:** Allow brushes and rollers to dry naturally and store them in a dry, dust-free place.
5. **Allowing solids to settle:** Allow the paint solids to settle at the bottom of the container. Once settled, pour the clear water into another container for reuse or disposal.

6. **Responsible Disposal:** Let the remaining paint solids dry out completely and dispose of them as solid waste.

Do not flush paint down the drain, including when cleaning painting tools

For professional cleaning tips, check out this video created in partnership with the British Coatings Federation and Dulux Connect contractor Bagnall's:

<https://coatings.org.uk/general/custom.asp?page=HowToCleanPaintbrushes>

When this paint container is empty please ask your stockist about recycling. If you have leftover paint, please dispose of it responsibly and consider donating it to **Community RePaint**. Find out more at duluxtrade.co.uk/sustainability.

Transportation & Storage

Do not use or store in extremes of temperature and protect from frost. To prevent spillage, please store and transport upright.

VOC

EU limit value for this product (cat.: A/a): 30g/l (2010).

Ready Mixed: This product contains max. 1g/l VOC. VOC content: Trace (0- 0.1%).

Tinted Colour: This product contains max. 1g/l VOC. VOC content: Trace (0- 0.1%).



ULTRA MATT INTERIOR WALLS

FURTHER SUPPORT

If you need further support, please contact the **AkzoNobel** Technical Advice Centre on 0333 222 70 70.

**** Mouldshield** Fungicidal Eggshell and DT Durable Kitchen and Bathroom Eggshell contain: 3-iodo-2-propynyl-n-butyl carbamate.

Use biocides safely. Always read the label and product information before use.

Always read full Health, Safety & Environmental Information on can before use.

Safety datasheet is available free on request by telephoning the **AkzoNobel** Technical Advice Centre or by visiting ***duluxtrade.co.uk***.

AkzoNobel, the AkzoNobel logo, the Flourish logo, Dulux Trade, Mouldshield, Polycell, Polyfilla and Community RePaint are trademarks of the AkzoNobel group. © AkzoNobel 2026.