

DESCRIPTION

Albany ABX Exterior Satin is a high-quality, vapour-permeable coating designed for multi-surface application. It offers supreme protection for a wide variety of new or previously painted surfaces, including concrete, glass, plastic, and both ferrous and non-ferrous metals. The self-priming formula delivers a durable, smooth satin appearance with minimal preparation. All while offering up to 15 year all weather protection.

RECOMMENDED USES



Suitable to use on timber, masonry, plastic, cladding, concrete, glass, ferrous and non-ferrous metal, for internal and external situations.

COVERAGE



A guide to the practical coverage which can be achieved under normal conditions is up to 12m² per litre on smooth surfaces.

DRYING TIME



Under normal drying conditions touch dry in 2 hours, recoatable after 4 - 6 hours. Allow for adequate ventilation during the drying period.

PROPERTIES

COMPOSITION

Pigment: Titanium dioxide, coloured pigments and extenders

Binder: Vinyl acetate copolymer

Solvent: Water

FINISH	Satin
FILM THICKNESS	Wet 110um. Dry 44um.
VOLUME SOLIDS	40% White. Other colours will vary.
FLASH POINT	Not Applicable

VOC CONTENT

EU limit value for this product (Cat A/i): 140 g/L (2010).

This product contains max 140 g/L VOC.

MEDIUM VOC CONTENT 8%-24.99%

LIMITATIONS

Do not apply when air or substrate temperatures are likely to fall below 10°C or when relative humidity is above 80% during application or the drying period.

AVAILABILITY



COLOUR RANGE

Available in the Albany colour ranged. Refer to current Albany literature.



PACK SIZES

1, 2.5 & 5 Litres.

KEY BENEFITS

- Self-Priming
- Stain Blocking
- Rust Inhibiting*

* While Albany ABX Exterior is self-priming on most substrates, you should spot prime knots, sap streaks, and any visible rust where necessary with a suitable primer prior to painting.

PREPARATION

For best results, ensure all surfaces to be painted are clean, dry and free from dust, grease, loose or flaking material. Bare surfaces should be primed with a suitable primer. Previously gloss-painted surfaces should be thoroughly abraded using fine waterproof abrasive paper and rinsed clean to ensure good adhesion. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding.

APPLICATION

Stir well before use. Apply by brush, roller or spray.

Apply two to three coats as required.

When applied on a Ferrous substrate, make sure to apply three coats to obtain the anticorrosion properties



THINNING / MIST COAT

For sealing new/bare surfaces add up to 1-part clean water to 10 parts paint.



AIRLESS SPRAY APPLICATION

For normal use thin up to 10%

(1 part water to 10 parts paint).

To achieve best results, use a 515, 517 or 519 tip

@1300-2500 psi (89-172 bar) (Tip dependant)

The above recommendations are intended as a guide only.

CLEANING UP



Remove as much product as possible from equipment before cleaning. Clean equipment immediately after use with warm soapy water and rinse thoroughly.

AFTER-CARE

MAINTENANCE

Between maintenance redecoration surfaces may be washed with a warm water and liquid detergent solution to remove surface dirt.

STORAGE

Avoid temperature extremes and protect from frost. Store and transport upright to prevent spillage.

HEALTH & SAFETY

- When preparing pre-1960s painted surfaces, take special precautions as they may contain harmful lead.
- Avoid contact with skin and eyes.
- Do not ingest.
- Store away from children and animals.
- Keep containers closed. Do not empty into drains, watercourses or septic tanks, including when cleaning tools. Some local authorities provide specialist facilities for the disposal of waste coatings.